

High Performance In-Counter Scanner and Scanner/Scale

The Magellan 8300 bi-optic scanner is a high performance 5-sided scanner for medium volume checkout environments. It offers great performance, high quality and reliability, and outstanding value. It improves operational efficiency by achieving outstanding first-pass read rates and represents the next step in value and checkout productivity from the Magellan family and Datalogic Scanning.

The 8300 can be configured as either scanner or scanner/scale combination with Datalogic's exclusive, patented All-Weighs® scale platter to ensure accurate produce and bulk food weighing at the checkout. Two remote scale display options are available; a single display on a pole and a dual display on a single pole for applications requiring separate displays for the cashier and customer. Magellan 8300 models are available in three lengths: long, medium, and short (scanner only) to accommodate various POS configurations.

FirstStrike® advanced software decoding algorithms provide the industry's best scanning speed and simultaneously

improve first pass read rates of damaged, wrinkled, or poorly printed bar codes delivering improved operational efficiencies at the retail checkout.

Flash memory allows for easy software upgrades that help extend the life of the retailer's investment. In addition, an auxiliary RS-232 port can be utilized in a variety of ways, including adding a handheld scanner, programming and configuring the scanner, or accessing the scanners label data output. For applications requiring electronic article surveillance (EAS), the 8300 can be equipped with Checkpoint EAS and can support aftermarket integrated Sensormatic EAS antennas with good read acknowledgement via the auxiliary RS-232 port. Optional Value Added Features provide optional information tools that help decrease front-end costs by managing information on scanner software and diagnostics.

Features

- Aggressive and ergonomic 360°
 5-sided scanning for best in class scanning performance
- Renowned Magellan brand quality and reliability
- All-Weighs Scale Platter with integrated Produce Lift Bar or Produce Rail™ (Optional)
- FirstStrike advanced decoding software delivers the best performance in reading poor quality labels
- Flash memory for easy software upgrades in the field
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Supports GS1 DataBar™ codes
- Checkpoint Systems and Sensormatic EAS compatible (Optional)
- Optional Value Added Features:
 - Host Download Lowers Service Cost and Improves Operations
 - Diagnostic Reporting For improved preventative maintenance
- Compatible with Mettler, Bizerba and other adaptive scales

www.scanning.datalogic.com



COLONIA TACO

Specifications

DECODING CAPABILITY

1D / LINEAR CODES Autodiscriminates all standard 1D codes including GS1 Databar™

linear codes

STACKED CODES GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar

Stacked Omnidirectional

ELECTRICAL

AC Input: 100-250 VAC, 50-60 Hz AC POWER REQUIREMENTS

Power Consumption: Operating (Maximum): 8 Watts

Operating (Nominal): 7 Watts Sleep Mode: 4 Watts

ENVIRONMENTAL

ESD PROTECTION (AIR DISCHARGE) HUMIDITY (NON-CONDENSING)

TEMPERATURE

Operating: 10 to 40 °C / 50 to 104 °F

Storage/Transport: -40 to 70 °C / -40 to 158 °F

INTERFACES IBM 46xx; Keyboard Wedge: Scanner Only; OEM (IBM) USB; RS-232;

USB: Scanner Only

AUXILIARY PORTS EAS Port: Powered RS-232; Remote Scale Display; Scale Host

5 - 95%

OPTIONAL FEATURES

ALL-WEIGHS SCALE PLATTER Integrated Produce Lift Bar; Produce Rail™

EAS FEATURES Checkpoint Systems: Integrated EAS hardware will work with

Counterpoint IV, V, VI and VII models; Sensormatic: Good Read Acknowledgement

Diagnostic Reporting; Host Download VALUE ADDED FEATURES

PHYSICAL CHARACTERISTICS

DIMENSIONS Depth (Below Counter): 10.2 cm / 4.0 in Height (Above Counter): 13.0 cm / 5.1 in

Length: Model 8301 (Short, Scanner Only): 35.6 cm / 14.0 in Model 8302 (Medium, Scanner Only): 40.1 cm / 15.8 in Model 8303 (Long, Scanner Only): 50.8 cm / 20.0 in Model 8304 (Medium, Scanner/Scale): 40.1 cm / 15.8 in Model 8305 (Long, Scanner/Scale): 50.8 cm / 20.0 in

Width: 29.2 cm / 11.5 in

SCALE CAPACITIES Adjustments Required: Calibration Only

Capacity: 15.0 kg / 30.0 lb

Maximum Static Weight: 68.0 kg / 150.0 lb Minimum Increment: 0.005 kg / 0.010 lb Vibration Immunity: 4 Programmable Filter Settings

READING PERFORMANCE

MOTOR SPEED 4,500 rpm **READ HEIGHT** 15.2 cm / 6.0 in READ RATE (MAXIMUM) 3.900 lines/sec.

Beeper (Adjustable Tone and Volume); Good Read LED READING INDICATORS

SCAN LINES 52 **SCAN ZONE** 360° SIDES READ 5 Sides

SAFETY & REGULATORY

AGENCY APPROVALS The product meets necessary safety and regulatory approvals for its

The Quick Reference Guide for this product can be referred to for a

complete list of certifications.

ENVIRONMENTAL COMPLIANCE Complies to EU RoHS

LASER CLASSIFICATION Caution Laser Radiation - Do not stare into beam; CDRH Class Ila

EN 60825 Class 1; IEC 60825 Class 1

UTILITIES

OPOS / JAVAPOS JavaPOS Utilities are available for download at no charge

OPOS Utilities are available for download at no charge

WARRANTY 1-Year Factory Warranty

- Reprints leaved. - The class of the lanest extent under U.S. and international laws.
 - Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo is a trademark of Datalogic

First Strike, All Weighs and Magellan are registered trademarks of Datalogic Scanning Inc. and OmegaTek and Produce Rail are trademarks of Datalogic Scanning Inc.

Other brand and product names may be trademarks of their respective owners.

www.scanning.datalogic.com