



## On-Counter Vertical Presentation Scanner

The Magellan 2200VS scanner is specifically designed for retailers that require high performance in a compact, vertical form factor. Tailored for very small counter retail checkout environments with medium to high volume point-of-sale (POS) transactions, the Magellan 2200VS scanner is particularly effective in drug stores, convenience stores, smaller to medium sized grocery stores, DIY stores, and specialty stores. With category leading scanning performance for superior ergonomics and throughput, the 2200VS demonstrates the Magellan brand renowned quality and reliability.

Advanced software decoding algorithms provide the industry's best scanning speed and simultaneously improve first pass read rates of damaged, wrinkled, or poorly printed bar codes delivering improved operational efficiencies at the retail checkout.

Flash memory allows for easy software upgrades that help extend the life of the

retailer's investment. In addition, an auxiliary RS-232 port can be utilized in a variety of ways, including adding a handheld scanner, programming and configuring the scanner, or accessing the scanner's label data output. For applications requiring electronic article surveillance (EAS), the 2200VS can be equipped with Checkpoint EAS and can support Sensormatic EAS systems with good read acknowledgement via the auxiliary RS-232 port. Optional Value Added Features provide optional information tools that help decrease front-end costs by managing information on scanner software and diagnostics.



## Features

- World's leading vertical on-counter single plane presentation bar code scanner
- Renowned Magellan brand quality and reliability
- Best in class scanning performance for both sweep and presentation scanning styles
- FirstStrike advanced decoding software delivers the best performance in reading poor quality labels
- Supports GS1 DataBar™ codes
- Flash memory for easy software upgrades in the field
- Multiple interface solution supports all popular host interfaces in every unit
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Checkpoint Systems and Sensormatic EAS compatible (Optional)
- Value Added Features:
  - Diagnostic Reporting - For improved preventative maintenance
  - Productivity Index Reporting™ - Helps identify poorly printed labels (Optional)

[www.scanning.datalogic.com](http://www.scanning.datalogic.com)



## Specifications

### DECODING CAPABILITY

#### 1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes

#### STACKED CODES

GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

### ELECTRICAL

#### AC POWER REQUIREMENTS

AC Input: 90-265 VAC, 47-63 Hz  
Power Consumption: Operating (Maximum): 9.6 Watts  
Operating (Nominal): 4.0 Watts  
2.5 Watts

#### SLEEP MODE

### ENVIRONMENTAL

#### ESD PROTECTION (AIR DISCHARGE)

25 kV

#### HUMIDITY (NON-CONDENSING)

5 - 95%

#### TEMPERATURE

Operating: 10 to 40 °C / 50 to 104 °F

Storage/Transport: -40 to 70 °C / -40 to 158 °F

### INTERFACES

#### AUXILIARY PORTS

IBM 46xx; Keyboard Wedge; OEM (IBM) USB; RS-232; USB  
Powered RS-232

### OPTIONAL FEATURES

#### EAS FEATURES

Checkpoint Systems: Integrated EAS hardware will work with Counterpoint IV, V, VI and VII models

Sensormatic: Good Read Acknowledgement

Diagnostic Reporting; Productivity Index Reporting™ (PIR)

#### VALUE ADDED FEATURES

### PHYSICAL CHARACTERISTICS

#### DIMENSIONS

15.2 x 15.2 x 9.7 cm / 6.0 x 6.0 x 3.8 in

#### WEIGHT

1.1 kg / 2.5 lb

### READING PERFORMANCE

#### MOTOR SPEED

6,000 rpm

#### READ HEIGHT

15.2 cm / 6.0 in

#### READING INDICATORS

Beeper (Adjustable Tone and Volume)

#### SCAN LINES

20

### SAFETY & REGULATORY

#### AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

The Quick Reference Guide for this product can be referred to for a complete list of certifications.

#### ENVIRONMENTAL COMPLIANCE

Complies to EU RoHS

#### LASER CLASSIFICATION

Caution Laser Radiation - Do not stare into beam; CDRH Class IIa  
EN 60825-1 Class 1

### UTILITIES

#### OPOS / JAVAPOS

JavaPOS Utilities are available for download at no charge  
OPOS Utilities are available for download at no charge

### WARRANTY

1-Year Factory Warranty

© 2005-2008 Datalogic Scanning Inc.

Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo is a trademark of Datalogic S.p.A.

FirstStrike and Magellan are registered trademarks of Datalogic Scanning Inc. and OmegaTek is a trademark of Datalogic Scanning Inc.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-MAGELLAN2200VS-EN 20080724

[www.scanning.datalogic.com](http://www.scanning.datalogic.com)