



- Write up to 300 times on the same card
- No ribbon or cartridge required
- Full ISO 3-Track Magnetic Strip Read/Write compatible

Perfect Solution for:

- Loyalty Applications
- Temporary Identification Cards
- Appointment Reminder Cards
- Event Credentials
- Membership Cards
- Mass Transit Pass
- Gaming Players' Cards



## TCP400 Thermal Re-Writable Card Reader/Writer

The TCP400 series offers the latest generation of Visual Card Reader/Writer systems. The TCP400 is a printer device which is used to write and erase information on 30 Mills thick cards. Information like loyalty points and special promotions can be updated any time the card is entered into the printer device. The unique dual pass head can provide clear text, barcodes, photos or other high quality graphics at 60mm/second. The TCP series are compact and streamlined units that will fit into any environment and are simple to operate. The card is simply inserted into the front of the unit, updated and automatically ejected in as little as 4 seconds.

Keep your customers with updated loyalty card!



# TCP400 Specifications

The Complete POS Solution!		
<b>Features</b>	<b>Hardware</b> High Quality Graphic & Text Print Supports Leuco Card Card Thickness 0.68mm to 0.84mm 3-Track Magnetic Stripe Read / Write Capability ISO Standard 7811/4,5 Card Media Re-Writable up to 500 Times Swappable Communication Interface Small Foot Print Built-in Universal Power Supply Simple Maintenance w/ Cleaning Required Notification LED Field Maintainable Design	<b>Software</b> Windows Raster Driver OCX Driver (ActiveX Control) Card Setting Utility Demo Utility & Sample Code for System Development
<b>Connectivity</b>	9-pin Serial 25-pin Serial Parallel USB Powered USB <b>Ethernet</b> Wi-Fi	<b>Dual 9-Pin Serial / USB</b> Virtual Serial Port to USB Virtual Serial Port to Ethernet
	Note: Connections in <b>bold</b> are supported; grayed-out connection types may be supported by special demand.	
<b>Drivers</b>	<b>Windows</b> <b>98, ME</b> <b>NT 4.0</b> WEPOS <b>2000, XP</b> <b>CE</b> <b>XP Embedded</b> <b>VISTA</b>	OPOS Java POS Linux Mac OSX
	Note: Drivers in <b>bold</b> are immediately available; grayed-out operating systems may be supported on request.	
<b>What's Included</b>	Cleaning Card User Manual Installation CD Ferrite Core (USB, Ethernet models)	
<b>Optional Accessories</b>	Putty or Gray Color Housing Available as Mechanism for kiosk Application Interface Cover Cleaning Kit	
<b>Technical Specifications</b>	Print Method : Direct Thermal Print Speed : 400mm/s (When Accessing Magnetic Stripe), 30mm/s (When Printing Leuco Card) Media : Leuco Card Size : 85.6mm x 54mm Card Thickness : 0.68mm to 0.84mm Magnetic Stripe : 3-Track Read / Write ISO 7811/4,5 Support	Power: AC 90 to 132V, 50 / 60Hz AC 198 to 264V, 50Hz Resolution: 203dpi Dimensions: W=119mm, H=132.5mm, D=270.5mm
<b>Warranty</b>	For US and Canada: 3-year Limited Warranty	
<b>For Further Information</b>	Sales: 1-800-782-7636 x107 Technical Support: 1-800-782-7636 x105	Web: <a href="http://www.starmicronics.com">http://www.starmicronics.com</a>